



Distributed by:  
 Laguna Clay Company  
 14400 Lomitas Ave  
 City of Industry, CA 91746  
 1-800-4Laguna  
 info@lagunaclay.com  
 www.lagunaclay.com

**SAFETY DATA SHEET**  
**Burnt Umbers - US**  
 Laguna Clay Company #MUMBB

## 1. Identification

### Product identifier

**Product name** Burnt Umbers - US  
**Product number** BU5250F,BU5350F,BU5452

### Recommended use of the chemical and restrictions on use

**Application** Industrial color

### Details of the supplier of the safety data sheet

**Supplier** Huntsman Pigments Americas LLC  
 P.O. Box 4980  
 The Woodlands, TX 77387  
 +1 301 210 3400 / +1 323 269 7311  
 MSDS@huntsman.com

### Emergency telephone number

**Emergency telephone** CHEMTREC: (800) 424-9300 (Contract No: 191118)

## 2. Hazard(s) identification

### Classification of the substance or mixture

**Physical hazards** Not Classified  
**Health hazards** Carc. 1A - H350 STOT RE 2 - H373  
**Environmental hazards** Not Classified

### Label elements

#### Pictogram



**Signal word** Danger

**Hazard statements** H350 May cause cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements** P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe vapor/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P308+P313 If exposed or concerned: Get medical advice/attention.  
 P314 Get medical advice/attention if you feel unwell.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with national regulations.

**Contains** CRYSTALLINE SILICA

## Burnt Umbers - US

### Other hazards

This product does not contain any substances classified as PBT or vPvB.

### 3. Composition/information on ingredients

#### Mixtures

<b>Umber</b>	<b>&gt; 90</b>
CAS number: 12713-03-0	REACH registration number: Proprietary

**Classification**  
Not Classified

<b>CRYSTALLINE SILICA</b>	<b>5-10%</b>
CAS number: 14808-60-7	

**Classification**  
Carc. 1A - H350  
STOT RE 2 - H373

<b>C.I. PIGMENT YELLOW 42</b>	<b>&lt; 5</b>
CAS number: 51274-00-1	
REACH registration number: Proprietary	

**Classification**  
Not Classified

<b>C.I. PIGMENT RED 101</b>	<b>&lt; 5</b>
CAS number: 1309-37-1	
REACH registration number: Proprietary	

**Classification**  
Not Classified

The Full Text for all Hazard Statements are Displayed in Section 16.

**Composition comments** 'Burnt Umbers' / 'Raw Umbers' Naturally occurring mixture of Fe<sub>2</sub>O<sub>3</sub>/MnxOy/SiO<sub>2</sub>/Al<sub>2</sub>O<sub>3</sub>/H<sub>2</sub>O

### 4. First-aid measures

#### Description of first aid measures

<b>Inhalation</b>	If exposed to excessive levels of dust or fumes, remove to fresh air. Get medical attention if cough or other symptoms develop.
<b>Ingestion</b>	Rinse mouth thoroughly with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed by medical personnel. Get medical attention if symptoms occur.
<b>Skin Contact</b>	Wash with soap and water. Get medical attention if irritation develops or persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if any discomfort continues.

### 5. Fire-fighting measures

#### Extinguishing media

## Burnt Umbers - US

**Suitable extinguishing media** The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Extinguish with the following media: Water spray, foam, dry powder or carbon dioxide.

### Special hazards arising from the substance or mixture

**Flammability Class** No Uniform Fire Code noted.

### Advice for firefighters

**Protective actions during firefighting** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Special protective equipment for firefighters** Wear self-contained breathing apparatus as combustion may produce hazardous fumes.

## 6. Accidental release measures

### Methods and material for containment and cleaning up

**Methods for cleaning up** If dust is generated, use appropriate respiratory protection. Vacuum or sweep up material and place in a disposal container. Avoid generation and spreading of dust. Large Spillages: Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Flush contaminated area with plenty of water. Avoid runoff into storm sewers and ditches which lead to waterways.

## 7. Handling and storage

### Precautions for safe handling

**Usage precautions** Minimize dust generation and accumulation. Do not breathe dust. Avoid contact with skin and eyes. Wash contaminated skin thoroughly after handling.

### Conditions for safe storage, including any incompatibilities

**Storage precautions** Store dry at ambient temperature away from food and beverages, excessive heat or flame sources (furnace, kilns, boilers etc.). Store away from substances subject to catalytic decomposition by dust, e.g. peroxides

## 8. Exposure Controls/personal protection

### Control parameters

### Occupational exposure limits

#### CRYSTALLINE SILICA

Long-term exposure limit (8-hour TWA): ACGIH 0.025 mg/m<sup>3</sup> respirable fraction  
A2

#### C.I. PIGMENT RED 101

Long-term exposure limit (8-hour TWA): OSHA 10 mg/m<sup>3</sup> fume  
Long-term exposure limit (8-hour TWA): OSHA 15 mg/m<sup>3</sup> total dust  
Long-term exposure limit (8-hour TWA): OSHA 5 mg/m<sup>3</sup> respirable fraction  
Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m<sup>3</sup> respirable fraction  
A4

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

A2 = Suspected Human Carcinogen.

A4 = Not Classifiable as a Human Carcinogen.

## Burnt Umbers - US

**Ingredient comments** Although no exposure limit has been established by OSHA for this product, the limit for nuisance particulates should be followed: OSHA 8-hr TWA 10mg/m<sup>3</sup> Total Dust 5 mg/m<sup>3</sup> respirable dust. ACGIH TLV-TWA 10mg/m<sup>3</sup> Total dust or 5mg/m<sup>3</sup> respirable dust.

### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Dusty powder.
<b>Color</b>	Light brown. to Dark brown.
<b>Odor</b>	Odorless.
<b>Odor threshold</b>	Not available.
<b>Melting point</b>	> 1000 deg C / 1832 deg F
<b>Initial boiling point and range</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Bulk density</b>	Not available.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not available.
<b>Volatile organic compound</b>	None.

### 10. Stability and reactivity

<b>Reactivity</b>	No information available.
<b>Stability</b>	No particular stability concerns.
<b>Materials to avoid</b>	Substances subject to catalytic decomposition caused by dust such as peroxides. Further avoid contact with aluminum dust, calcium hypochlorite, hydrazine, ethylene oxide, caesium carbide.

### 11. Toxicological information

## Burnt Umbers - US

### Information on toxicological effects

<b>Toxicological effects</b>	No specific toxicity tests have been carried out on this product.
<b>Inhalation</b>	Frequent inhalation of dust over a long period of time increases the risk of developing lung diseases.
<b>Ingestion</b>	No harmful effects expected from quantities likely to be ingested by accident.
<b>Skin Contact</b>	Substance may cause slight skin irritation.
<b>Eye contact</b>	May cause slight irritation.

### 12. Ecological Information

**Ecotoxicity** There are no data on the ecotoxicity of this product.

#### Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

#### Bioaccumulative potential

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### Mobility in soil

**Mobility** No data available.

#### Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### Other adverse effects

**Other adverse effects** None known.

### 13. Disposal considerations

#### Waste treatment methods

**General information** Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

### 14. Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DoT).

### 15. Regulatory information

#### US Federal Regulations

##### **SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

##### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

None of the ingredients are listed or exempt.

##### **SARA 313 Emission Reporting**

## Burnt Umbers - US

Manganese Compound  
1.0 %

### CAA Accidental Release Prevention

Manganese Compound  
1.0 %

### US State Regulations

#### California Proposition 65 Carcinogens and Reproductive Toxins

CRYSTALLINE SILICA  
5-10%

#### Massachusetts "Right To Know" List

C.I. PIGMENT RED 101  
Present.

CRYSTALLINE SILICA  
Present.

#### Rhode Island "Right To Know" List

C.I. PIGMENT RED 101  
Present.

CRYSTALLINE SILICA  
Present.

#### Minnesota "Right To Know" List

C.I. PIGMENT RED 101  
Present.

CRYSTALLINE SILICA  
Present.

#### New Jersey "Right To Know" List

C.I. PIGMENT RED 101  
Present.

CRYSTALLINE SILICA  
Present.

#### Pennsylvania "Right To Know" List

C.I. PIGMENT RED 101  
Present.

CRYSTALLINE SILICA  
Present.

### Inventories

#### EU - EINECS/ELINCS

EINECS  
All the ingredients are listed or exempt.

#### Canada - DSL/NDL

DSL  
All the ingredients are listed or exempt.

#### US - TSCA

## Burnt Umbers - US

All the ingredients are listed or exempt.

### US - TSCA 12(b) Export Notification

No.

### Australia - AICS

All the ingredients are listed or exempt.

### Japan - MITI

#### C.I. PIGMENT YELLOW 42

No.

#### C.I. PIGMENT RED 101

Yes

#### Umber

No.

### Korea - KECI

All the ingredients are listed or exempt.

### China - IECSC

All the ingredients are listed or exempt.

### Philippines - PICCS

All the ingredients are listed or exempt.

### New Zealand - NZIOC

All the ingredients are listed or exempt.

## 16. Other information

<b>Revision date</b>	8/19/2015
<b>Revision</b>	5
<b>Supersedes date</b>	7/7/2015
<b>SDS No.</b>	17758
<b>Hazard statements in full</b>	H350 May cause cancer. H373 May cause damage to organs through prolonged or repeated exposure. H373 May cause damage to organs (Lungs) through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.