| Product Names: Synonym/s: | Navajo Brand Pumice Grades 0, 4/0, F, FF, FFF, FFFF Pumice, Volcanic Glass | | |
|------------------------------------|---|--|--|
| Manufacturer: | www.lagunaclay.com | | |
| | CR Minerals | | |
| | P.O. Box 708 | | |
| | Ohkay Owingeh, NM 87566 | | |
| | 505-428-2940 | | |
| Emergency Phone: | Chemtrec 1-800-424-9300 | | |
| Chemical Name: Chemical Family: | Pumice (Amorphous Metal silicates) | | |
| Chemical Formula: | M _x O _y .SiO2 (M=AI, Ca, Mg + other minor metal oxides bound with SiO2) | | |
| Product Use/s: | Abrasive, Filter Media, Light weight aggregate, Pozzolan | | |
| Prepared By: | CR Minerals | | |

| SECTION 2: COMPOSITION / INFORMATION ON INGREDIENTS | | | | | | |
|---|------------|-----------------------------------|------------------------------------|------------------------------------|-----------------------|--------------|
| Ingredient | CAS | OSHA PEL, TWA 8/40h (mg/m3) | ACGIH TLV, TWA 8/40h (mg/m3) | NIOSH REL, TWA 8/40h (mg/m3) | NIOSH IDLH (mg/m3) | Conc. (%) |
| Pumice (Amorphous metal silicates) | 1332-09-8 | 15 (total dust) 5 (respirable) | 10 | 10 (total dust) 5 (respirable) | N.A. | > 90 |
| Crystalline Silica, SiO ₂ (Quartz) | 14808-60-7 | 10/(SiO2% + 2) (respirable) | 0.025 (respirable) | 0.05 (respirable) | 50 | < 1% |

| OSHA Regulatory Status: This material is subject to 29 CFR 1910.1200 (Hazard Communication). | | | | |
|--|--|--|--|--|
| SECTION 3: HAZARDS IDENTIFICATION | | | | |
| Emergency Overview: | Pumice is an odorless white or grayish-white material that ranges from pebble to a granular powder. Contact can cause irritation to eyes, skin, respiratory system, and gastrointestinal tract. | | | |
| Potential Health Effects | | | | |
| Eyes: | Contact can cause irritation of eyes. | | | |
| Skin: | Contact can cause mild irritation of skin. | | | |
| Ingestion: | This product can cause mild irritation of gastrointestinal tract if swallowed. | | | |
| Inhalation: | This product can cause mild irritation of the respiratory system. Long-term exposure may cause permanent damage. Pumice is not listed by MSHA, OSHA, or IARC as a carcinogen. However, this product may contain trace amounts of crystalline silica in the form of quartz or crystobalite, which has been classified by IARC as a Group I carcinogen to humans when inhaled. Inhalation of silica can also cause a chronic lung disorder, silicosis. | | | |
| Medical | | | | |
| Conditions Aggravated by Exposure: | Contact may aggravate disorders of the eyes, skin, gastrointestinal tract, and respiratory system. | | | |
| Potential Environmental Effects: | Pumice is an inert material. | | | |

www.Lagunaclay.com

| Eyes: | Immediately flush eyes with generous amounts of water or eye wash solution if water is unavailable. Pull back eyelid while flushing to ensure that all dust has been washed out. Seek medical attention promptly if the initial flushing of the eyes does not remove the irritant. Do not rub eyes. |
|-------------|--|
| Skin: | Brush off or remove as much dry dust as possible. Wash exposed area with large amounts of water. If irritation persists, seek medical attention promptly. |
| Inhalation: | Move victim to fresh air. Seek medical attention. If breathing has stopped, give artificial respiration. |
| Ingestion: | Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth unless instructed to do so by medical personnel. |

SECTION 5: FIRE FIGHTING MEASURES

| Fire Hazards: | Pumice is not combustible or flammable. This product is not considered to be an explosion hazard. |
|-----------------------------|---|
| Hazardous | |
| Combustion Products: | None |
| Extinguishing Media: | Use extinguishing media appropriate for surrounding fire. |
| Fire | |
| Fighting Instructions: | Keep personnel away from and upwind of fire. Avoid skin contact or inhalation of dust. |
| | Wear full fire-fighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). |

SECTION 6: ACCIDENTAL RELEASE MEASURES

| Spill / Leak Procedures: | Use proper protective equipment. |
|--------------------------|---|
| Small Spills: | Use dry methods to collect spilled materials. Avoid generating dust. Do not clean up with compressed air. Store collected materials in dry, sealed plastic or non-aluminum metal containers. Residue on surfaces may be water washed. |
| Large Spills: | Use dry methods to collect spilled materials. Evacuate area downwind of clean-up operations to minimize dust exposure. Store spilled materials in dry, sealed plastic or non-aluminum metal containers. |
| Containment: | Minimize dust generation and prevent bulk release to sewers or waterways. |
| Clean-up: | Residual amounts of material can be flushed with large amounts of water. Equipment can be washed with either a mild vinegar and water solution, or detergent and water. |

SECTION 7: HANDLING AND STORAGE Handling: Avoid forming dust. Keep in tightly closed plastic or metal containers. Protect container from physical damage. Avoid direct skin contact with the material. Storage: Store in a cool, dry, and well-ventilated location.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

| Engineering Controls: | Provide ventilation adequate to maintain PELs. | | | | |
|--------------------------------|--|--|--|--|--|
| Respiratory Protection: | Use NIOSH/MSHA approved respirators if airborne concentration exceeds PELs. | | | | |
| Skin Protection: | Use appropriate gloves and footwear to prevent skin contact and the potential for irritation. Clothing should fully cover arms and legs. | | | | |
| Eye Protection: | Use safety glasses with side shields or safety goggles. Contact lenses should not be worn when working in dusty environment. | | | | |
| Other: | Eye wash fountain/stations and emergency showers should be available. | | | | |
| www.Lagunaclay.d | com 800-452-4862 info@lagunaclay.com | | | | |

www.CRMinerals.com

for latest MSDS versions

2 of 4

| SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES | | | |
|---|------------------------|-------------------|--|
| Appearance: | Odor: | Physical State: | |
| White or grayish-white lumps or powder | Odorless | Solid | |
| Boiling Point (°C/°F): | Melting Point (°C/°F): | Specific Gravity | |
| N.A. | N.A. | 2.34 | |
| Vapor Pressure (mm Hg): | Vapor Density: | Evaporation Rate: | |
| N.A. | N.A. | N.A. | |
| Solubility in Water | pH (25°C/77°F): | | |
| Negligible solubility in water | 8 - 10 | | |

| LITY AND REACTIVITY | | | | |
|--|--|---|--|--|
| Chemically stable. | | | | |
| Pumice should not be mixed or stored with the following materials, due to the potential for vigorous reaction and release of heat: | | | | |
| Hydrofluoric Acid | | | | |
| | | | | |
| Decomposition Products: | None | | | |
| Polymerization: | None | | | |
| | Chemically stable. Pumice should not be mixed or st for vigorous reaction and release Hydrofluoric Acid Decomposition Products: | Chemically stable. Pumice should not be mixed or stored with the follow for vigorous reaction and release of heat: Hydrofluoric Acid Decomposition Products: None | | |

SECTION 11: TOXICOLOGICAL INFORMATION

An LD50 of 6450mg/kg (Rat, oral) has been identified for this product. Pumice is not listed by MSHA, OSHA, or IARC as a carcinogen, but this product may contain crystalline silica, which has been classified by IARC as carcinogenic to humans when inhaled in the form of quartz or crystobalite.

SECTION 12: ECOLOGICAL INFORMATION

| | Because of its unreactive nature, it would not be expected to produce ecotoxicity upon exposure to aquatic organisms and aquatic systems. |
|---------------------|---|
| Environmental Fate: | This material shows no bioaccumulation effect or food chain concentration toxicity. |

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable federal, state, and local environmental regulations. If this product as supplied, and unmixed, becomes a waste, it will not meet the criteria of a hazardous waste as defined under the U.S. Resource Conservation and Recovery Act (RCRA).

www.Lagunaclay.com

800-452-4862 Visit www.CRMinerals.com for latest MSDS versions

info@lagunaclay.com

SECTION 14: TRANSPORTATION INFORMATION

Pumice is not classified as a hazardous material by US DOT and is not regulated by the Transportation of Dangerous Goods (TDG) when shipped by any mode of transport.

SECTION 15: REGULATORY INFORMATION

| U.S. EPA Regulations: | RCRA Hazardous Waste Number (40 CFR 261.33): not listed_ RCRA Hazardous Waste Classification (40 CFR 261): not classified CERCLA Hazardous Substance (40 CFR 302.4) unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311(b)(4); CWA, Sec. 307(a), CAA, Sec. 112 CERCLA Reportable Quantity (RQ), not listed SARA 311/312 Codes: not listed SARA Toxic Chemical (40 CFR 372.65): not listed SARA EHS (Extremely Hazardous Substance) (40 CFR 355): not listed, Threshold Planning Quantity (TPQ): not listed All chemical ingredients are listed on the USEPA TSCA Inventory List. | | | | |
|--|---|------------------------------------|--------------------------------|--|--|
| OSHA/MSHA Regulations: | Air Contaminant (29 CRF 1910.1000, Table Z-1, Z-1-A): 5mg/M ³ TWA-8 MSHA: <u>not listed</u> OSHA Specifically Regulated Substance (29 CFR 1910): <u>not listed</u> | | | | |
| State Regulations: | Consult state and local authorities for guidance. Components found in this product may contain trace amounts of inherent naturally occurring elements (such as, but not limited to arsenic and cadmium) that may be regulated. California Proposition 65 lists respirable crystalline silica (10 microns) as a carcinogen. This product may contain respirable crystalline silica | | | | |
| Canada: | WHMIS Classification: "D2A" Materials Causing Other Toxic Effects Canada NDSL: Listed | | | | |
| EU Reach: | Navajo, PFM pumice are natural minerals and thus are explicitly exempted from regulations and evaluation. | | | | |
| Crystalline Silica: | R48/20: Harmi | ful: danger of serious | damage to healt | h by prolonged exposure through inhalation | |
| NFPA Hazard Class: HMIS Hazard Class: | Health: 1 Health: 1 | Flammability: 0 Flammability: 0 | Reactivity: 0 Reactivity: 0 | Specific Hazard: | |
| May | GHS: Warning be harmful if swa and enters airway | | | | |

SECTION 16: OTHER INFORMATION Prepared By: CR Minerals: July 2014

CR Minerals provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person. Individuals receiving this information must consult their own technical and legal advisors and/ or exercise their own judgment in determining its appropriateness for a particular purpose. CR Minerals makes no representations or warranties, either express or implied, including without limitation and warranties of merchantability or fitness for a particular purpose with respect to the information set forth herein or the product(s) to which the information refers. Accordingly, CR Minerals will not be responsible or Viver famages resulting from bound from bound for a failure information contained and be appropriate as a set of the information contained and be appropriate as a set of the information contained and warranties of merchantability or fitness for a particular purpose with respect to the information set forth herein or the product(s) to which the information refers. Accordingly, CR Minerals will not be responsible or

ay.comainages resulting norm bouts452-4662 apoint of railate informitagen Visit